

SILTEC

MINI MOBILE DEGREASING PARTS WASHER

THE PROFESSIONAL RANGE

DESCRIPTION

Working tank:

- 350 X 520 X 80
- Height, hood opened: 660mm
- Storage space

Maximum weight in the working tank:

- 50 Kg
- Pump flow: 15L /min
(Varies according to product density)
- Interchangeable cleaning brush
- Integrated emptying plug
- Utilisation capacity: 15 L
- Turning on simply by plugging to the mains (220V)
- Plug filter: inox
- Empty weight: 5 Kg
- Nominal power: 0.7 amperes
- Material: HDPE

455 mm

640 mm

PRECAUTIONS

CAUTION: NO FLAMMABLE PRODUCT IN THIS FOUNTAIN ONLY PRODUCTS IN ACQUEOUS PHASE

We decline any responsibility in case of introduction of volatile and/or flammable products such as: alcohol, fuel, etc. which would lead to explosion risks and/or fire, and can be harmful for others' lives and/or can destroy goods..

The information in our brochures, letters, reviews and reports is provided to advise you especially regarding testing that has been carried out, with an ongoing concern for objectivity and without any commitment on our part.

PACKAGING

1 per case

260 mm

Notch at each side for
easy transport

We can equip your commercial
vehicles with this transformer



www.siltec-actalys.com

ACTALYS - ZA DU HAUT DES TAPPES - BP 70065 - 54310 HOMECOURT - FRANCE
TEL +33 3 82 20 67 50 - FAX +33 9 70 61 29 66 - SILTEC-ACTALYS@orange.fr